www.acer.es

Proyectores Prof. Mayo 2009

Lista de Precios

acer

DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS
PERIPHERALS
PC DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS
PERIPHERALS
PC DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS
PERIPHERALS
PC DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS
PERIPHERALS
PC DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS
PERIPHERALS
PC DESKTOP
NOTEBOOKS
SERVER/STORAGE
HANDHELDS

acer

P5280

Target User

- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- High-impact projection
- Optimal usability
- Versatile multimedia
- Complete functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Procesador de luz digital
Native Resolution	Nativa XGA (1,024 x 768)
Compressed Resolution	Máxima UXGA (1,600 x 1,200), WSXGA+(1,680x1,050)
Typical Colors	134 Milliones de colores
Brightness (ANSI lumens)	3,500 ANSI Lumens (Standard), 2,800 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Noise Level	34 dBA (Standard modo), 31 dBA (ECO modo)
Weight	3.0Kg (6.6 lbs)
Dimensions	299 x 229 x 93 mm (11.8"x 9.0"x 3.7")
Digital Zoom	2x
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	N/A
Aspect Ratio	4:3 (Nativo), 16:9 (Escalable)
Horizontal Scan Rate:	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection Distance	3.3' (1.0m) ~ 39'(12.0m)
Projection Screen Size (Diagonal):	23" (0.58m) ~ 300" (7.62m)
Keystone Correction	+/-40 Grados Correción Keystone Vertical Keystone
Audio	Un altavoz interno con 2 watts de salida
Lamp Life	2,000 Horas (Standard), 3,000 Horas (ECO)
Lamp Type	Lámpara de 260 W UHP reemplazable por el usuario
Power Consumption	355 Watts (Operation), 10 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1
Bundled Accesories	Cable de alimentación AC, Cable VGA, Cable de video compuesto, Cable DVI, Mando a distancia, Dos pilas para el mando a distancia, Maletín de transporte, Guía de usuario (CD-ROM), Guía de inicio rápida, Tarjeta de seguridad
Ceiling Mounting Capability	Si
Warranty	Todos los proyectores de Acer tienen 2 años de garantía carry-in y una garantía de 90 días en las lámparas.

Modelo	Part Number	Precio	
P5280 Eco , CBII, ZOOM, XGA , 3.0kg, '2000:1, 3500 Lm, UK/EUR/SWI Power	EY.J7501.001	EUR 672.00	

P5260E

Target User

- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Remarkable display
- Simple usability
- Flexible connectivity
- Thorough functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Procesador de Luz Digital
Native Resolution	Nativa XGA (1,024 x 768)
Compressed Resolution	Máxima UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical Colors	16.7 Millones de Colores
Brightness (ANSI lumens)	2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Contrast Ratio	2100:1
Noise Level	31 dBA (Standard mode), 29 dBA (ECO mode)
Weight	2.8Kg (6.2lbs)
Dimensions	300 x 228 x 100 mm (11.8”x 9.0”x 3.9”)
Digital Zoom	2x
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards UXGA, SXGA, XGA, SVGA, VGA (resizing)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	N/A
Aspect Ratio	4:3 (Nativa), 16:9
Horizontal Scan Rate:	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection Distance	3.3’ (1.0m) ~ 39.4’(12.0m)
Projection Screen Size (Diagonal):	23” (0.58m) ~ 300” (7.62m)
Keystone Correction	+/-40 Grados Corrección Keystone Vertical
Audio	Un altavoz interno con 2 vatios de salida
Lamp Life	3’000 Horas (Standard), 5’000 Horas (ECO)
Lamp Type	Lámpara P-VIP 230 W replazable por el usuario
Power Consumption	280 Watts (Operation), <5 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1
Bundled Accesories	Cable de corriente AC, Cable VGA, Cable de video compuesto, Cable DVI, Mando a distancia, Dos pilas para el mando a distancia, Maleta de transporte, Guía de usuario (CD-ROM), Guía rápida de usuario, Tarjeta de seguridad
Ceiling Mounting Capability	Si
Warranty	Todos los proyectores de Acer tienen dos años de garantía carry-in y una garantía de 90 días en la lámpara.

Modelo	Part Number	Precio	
P5260E DLP, ZOOM, XGA 1024x768, 3.0KG, ‘2000:1, 2700 LUMENS	EY.J6002.001	EUR 525.00	

P7270i

Target User

- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Splendid presentation
- Superior usability
- Multimedia pro
- Efficient functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Procesador de luz digital
Native Resolution	Nativa XGA (1,024 x 768)
Compressed Resolution	Máxima UXGA (1,600 x 1,200), WSXGA+ (1,680x1050)
Typical Colors	1.07 Billiones de colores
Brightness (ANSI lumens)	4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (ECO)
Contrast Ratio	2300:1
Noise Level	29 dBA (modo Standard), 27 dBA (modo ECO)
Weight	5Kg (11 lbs)
Dimensions	404 x 315 x 120 mm (15.9"x 12.4"x 4.7")
Wireless	Si
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	Si
Aspect Ratio	4:3 (Nativa), 16:9
Horizontal Scan Rate:	27 ~ 92 kHz
Vertical Scan Rate	50 ~ 85 Hz
Projection Distance	3.9' (1.2m) ~ 32.0'(9.8m)
Projection Screen Size (Diagonal):	31" (0.78m) ~ 300" (7.62m)
Keystone Correction	Corrección Keystone Vertical +/-40 Grados
Audio	2 altavoces internos con 3 vatios de salida cada uno
Lamp Life	2,000 Horas (Standard), 3,000 Horas (ECO)
Lamp Type	Lámpara P-VIP de 280 W remplazable por el usuario
Power Consumption	TBD Watts (Operation), TBD Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1, Network Audio (Stereo mini jack) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1, 802.11b/g wireless technology, Ethernet port (RJ45) x 1, Wireless antenna connector (SMA) x 1
Bundled Accesories	Cable de corriente AC, Cable VGA, Cable de video compuesto, Cable DVI, Cable S-Video, Cable Video por Componentes, Mando a distancia, Dos pilas para el mando a distancia, Antena desmontable, Wireless PnS Token, Base of Wireless PnS Token, Detachable cable holder, 2 x filtros de polvo Protector de lente, Maleta de transporte, Guía de usuario (CD-ROM), Guía rápida de usuario, Tarjeta de seguridad
Ceiling Mounting Capability	Yes
Warranty	Todos los proyectores de Acer tienen dos años de garantía carry-in y una garantía de 90 días en la lámpara.

Modelo	Part Number	Precio	
P7270i (CBII, Eco) , CBII, ZOOM, XGA , 5.4KG, '2300:1, 4000 Lm, WIFI, UK/EUR/SWI Power,HDMI, DVI.	EY.J7701.001	EUR 1206.00	

P5270

Target User

- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Bright, realistic display
- Convenient usability
- Multimedia excellence
- Comprehensive functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Digital Light Processor
Native Resolution	XGA 1024x768
Compressed Resolution	Resolución máxima UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	16.7 million colors
Brightness (ANSI lumens)	3,000 ANSI Lumens (Standard) - 2,400 ANSI Lumens (ECO)
Dimension (WxDxH)	299 x 229 x 93 mm (11.8"x 9.0"x 3.7")
Weight	3.0Kg (6.6 lbs)
Contrast Ratio	2000:1
Noise Level	28 dBA (ECO mode) - 31 dBA (Standard mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Zoom Manual y Zoom Focal
Projection Screen	23"(58cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Horizontal Scan	31.5-100KHz
Vertical Scan	56-85Hz
Lamp Type	Lámpara remplazable de 220 W UHP
Lamp Life	4,000 Horas (ECO) - 3,000 Horas (Standard)
Keystone Correction	+/-40 Grados (Vertical)
Audio	Un altavoz interno de 2 watts
Power Supply	Apagado automático de la fuente de alimentación (AC 100~240V)
Power Consumption	280 Watts (Operation), 10 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 DVI (HDCP) x 1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 2 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	Cable de alimentación AC Cable VGA Cable de video composite Cable DVI Mando a distancia Dos pilas para el mando a distancia Maletín de transporte Guía de usuario Guía de inicio rápida Tarjeta de seguridad
Warranty	Todos los proyectores de Acer tienen 2 años de garantía carry-in y una garantía de 90 días en las lámparas.

Modelo	Part Number	Precio	
P5270 Eco , CBII, ZOOM, XGA, 3.0KG, '2000:1, 3000 Lm, UK/EUR/SWI Power	EY.J7401.001	EUR 585.00	

S1200 - Ultra-short throw

Target User

- Usuarios domésticos/privados
- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Impressive, sophisticated presentation
- Environmentally friendly projection
- Empowering usability, prolific connectivity
- Enhanced functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Digital Light Display with ColorBoost II and EcoProjection
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	134 Million Colors
Brightness (ANSI lumens)	2,500 ANSI Lumens (Standard) 2,000 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 275 x 103 mm (10.6"x 10.8"x 4.1")
Weight	6.6 lbs (3.0 Kg)
Contrast Ratio	2000:1
Noise Level	32 dBA (Standard mode) 28 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.6, f = 6.97mm, Manual Focus
Projection Screen	41"(104cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	164"@2m or 82"@1m (0.60:1)
Projection Distance	1.6'(0.5m) ~ 12.0'(3.7m)
Horizontal Scan	31.5-100KHz
Vertical Scan	56-85Hz
Lamp Type	200 W user replaceable P-VIP lamp
Lamp Life	4,000 Hours (ECO) 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical)
Audio	One Internal Speaker with 8 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	275 Watts (Operation) <5 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Analog RGB (D-sub) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

Modelo	Part Number	Precio	
S1200 Eco , CBII, UST Lens, XGA, 3.0KG, '2000:1, 2500Lm, UK/EUR/SWI Power,HDMI.	EY.J8001.001	EUR 680.00	

P1270

Target User

- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Striking display
- Highly usable and empowering
- Environmentally friendly projection
- Enhanced functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Digital Light Display with Colorboost II and EcoProjection
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	134 Million Colors
Brightness (ANSI lumens)	3,100ANSI Lumens (Standard) 2,480 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 206 x 96 mm (8.8"x 6.7"x 3.1")
Weight	5.5 lbs (2.5 Kg)
Contrast Ratio	2000:1
Noise Level	31 dBA (Standard mode) 28 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.66, f = 18.17mm ~ 21.81mm 1:1.2 Manual Zoom and Manual Focus
Projection Screen	26"(65cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	62"@2m (1.60 ~ 1.92:1)
Projection Distance	3.3'(1.0m) ~ 32.0'(9.8m)
Horizontal Scan	31.5-100KHz
Vertical Scan	50-85Hz
Lamp Type	230 W user replaceable P-VIP lamp
Lamp Life	4,000 Hours (ECO) 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical)
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	300 Watts (Operation) <5 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Analog RGB (D-sub) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

Modelo	Part Number	Precio	
P1270 Eco, CBII,ZOOM, bag, XGA , 2.5KG, '2000:1, 3100 Lm	EY.J8101.001	EUR 560.00	

P5260i

Target User

- Soluciones profesionales y para la pequeña empresa
- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Fine details, lively imagery
- Expanded usability
- Advanced connectivity
- Integrated functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Procesador de luz digital
Native Resolution	Nativa XGA (1,024 x 768)
Compressed Resolution	Máxima UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical Colors	134 Milliones de Colores
Brightness (ANSI lumens)	2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Noise Level	31 dBA (Standard modo), 25 dBA (modo ECO)
Weight	6.6 lbs (3.0Kg)
Dimensions	299 x 229 x 93 mm (11.8"x 9.0"x 3.7")
Digital Zoom	2x
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	N/A
Aspect Ratio	4:3 (Nativa), 16:9
Horizontal Scan Rate:	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Projection Screen Size (Diagonal):	23"(58cm) ~ 300"(762cm)
Keystone Correction	+/-40 Grados (Vertical)
Audio	Un altavoz interno de 2 Watts de salida
Lamp Life	3,000 Horas (Standard), 4,000 Horas (ECO)
Lamp Type	Lámpra P-VIP Osram 200 W remplazable por el usuario
Power Consumption	255 Watts (Operation), 14 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 1, Analog RGB (D-sub) x 1, Network Audio (Stereo mini jack) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1, 802.11b/g wireless technology, Ethernet port (RJ45) x 1, Wireless antenna connector (SMA) x 1
Bundled Accesories	Cable de alimentación AC, Cable VGA, Cable de video compuesto, Cable DVI, Mando a distancia, Dos pilas para el mando a distancia, Antena desmontable, Wireless PnS token, PnS token holder, Maletín de transporte, Guía de usuario (CD-ROM), Guía rápida de inicio, Tarjeta de seguridad
Ceiling Mounting Capability	Si
Warranty	Todos los proyectores de Acer tienen 2 años de garantía carry-in y 90 días de garantía en la lámpra.

Modelo	Part Number	Precio	
P5260i Eco, CBII, ZOOM, XGA , 3.0KG, '2000:1, 2700 Lm, WIFI, UK/EUR/SWI Power	EY.J7301.001	EUR 801.00	

P7280

Target User

- Pequeñas y medianas empresas
- Grandes empresas

Key Selling Points

- Absorbing projection
- Versatile usability
- Complete connectivity
- Enhanced functionality

Configuración Standard (Puede variar dependiendo del modelo)

Display Technology	DLP™, Procesador de luz digital
Native Resolution	Nativa XGA (1,024 x 768)
Compressed Resolution	Máxima UXGA (1,600 x 1,200), WSXGA+ (1,680x1,050)
Typical Colors	1.07 Billiones de Colores
Brightness (ANSI lumens)	4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (ECO)
Contrast Ratio	2300:1
Noise Level	34 dBA (Standard modo), 29 dBA (modo ECO)
Weight	5Kg (11 lbs)
Dimensions	404 x 315 x 120 mm (15.9"x 12.4"x 4.7")
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	Si
Aspect Ratio	4:3 (Nativo), 16:9
Horizontal Scan Rate:	27 ~ 92 kHz
Vertical Scan Rate	50 ~ 85 Hz
Projection Distance	3.9'(1.2m) ~ 32.0'(9.8m)
Projection Screen Size (Diagonal):	31"(78cm) ~ 300"(762cm)
Keystone Correction	+/-40 Grados Corrección Keystone Vertical
Audio	Salida de 2 altavoces internos de 3 watts cada uno
Lamp Life	2,000 Horas (Standard), 3,000 Horas (ECO)
Lamp Type	Lámpra P-VIP de 330 W remplazable por el usuario
Power Consumption	TBD Watts (Operation), TBD Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1
Bundled Accesories	Cable de corriente AC, Cable VGA, Cable de video compuesto, Cable DVI, Cable S-Video, Cable Video por Componentes, Mando a distancia, Dos pilas para el mando a distancia, Detachable cable holder, 2 x filtros de polvo, Protector de lente, Maleta de transporte, Guía de usuario (CD-ROM), Guía rápida de usuario, Tarjeta de seguridad
Ceiling Mounting Capability	Si
Warranty	Todos los proyectores de Acer tienen dos años de garantía carry-in y una garantía de 90 días en la lámpara.

Modelo	Part Number	Precio	
P7280 Eco , CBII, ZOOM, XGA , 5.4KG, '2300:1, 4500 Lm, UK/EUR/SWI Power	EY.J7801.001	EUR 1163.00	